

DAFTAR PUSTAKA

- Aisyah, I. S., Rusdiantoa, M., & A. Fauzan Hery. (2020). *Studi Pemesinan Ti6246 Dengan Jatropha Curcas.* 72–79.
<http://research-report.umm.ac.id/index.php/sentra/article/view/3878/3809>
- Attia, N. K., El-Mekkawi, S. A., Elardy, O. A., & Abdelkader, E. A. (2020). Chemical and rheological assessment of produced biolubricants from different vegetable oils. *Fuel*, 271(September 2019), 117578.
<https://doi.org/10.1016/j.fuel.2020.117578>
- Becker, F. G., Cleary, M., Team, R. M., & Holtermann. (2015). Cairan Pendingin Untuk Proses Pemesinan. *Syria Studies*, 7(1), 37–72.
https://www.researchgate.net/publication/269107473_What_is_governance/link/548173090cf22525dc61443/download
%0A
http://www.econ.upf.edu/~reynal/Civil_wars_12December2010.pdf%0A
<https://think-asia.org/handle/11540/8282%0A>
<https://www.jstor.org/stable/41857625>
- Brookfield Engineering Labs. Inc. (2003). *More Solutions to Sticky Problems: A Guide to Getting More From Your Brookfield Viscometer.* 55.
- Farrag, N. M., Bayoumi, R. A., & Mohamed, T. A. (2022). Factorial analysis of nano-precipitated calcium carbonate via a carbonation route using Solvay wastewater. *Case Studies in Chemical and Environmental Engineering*, 6(July), 100236.
<https://doi.org/10.1016/j.cscee.2022.100236>
- Harold, M. (2004). *Crude Palm Oil (CPO) atau minyak kelapa sawit.* 3–19. [http://eprints.polsri.ac.id/975/3/BAB II.pdf](http://eprints.polsri.ac.id/975/3/BAB%20II.pdf)
- Journal, U., & Kunc, K. (2019). *PEMANFAATAN BATU KAPUR*

*SEBAGAI BAHAN BAKU HIDROKSIAPATIT
UTILIZATION OF LIMESTONE AS HYDROXYAPATITE
RAW MATERIAL Aprita Erin Wardiana , Fadlilah Gita
Shalli , Eka Candra Saputra , and Sari Edi Cahyaningrum *
Departement of Chemistry , Faculty of Matematic. 8(2).*

- Karmin, & Ginting, M. (2012). Analisis Peningkatan Kekerasan Baja Amutit Menggunakan Media Pendingin Dromus. *Jurnal Austenit*, 4(1), 1–7.
- Kedzierski, M. A. (2013). Viscosity and density of aluminum oxide nanolubricant. *International Journal of Refrigeration*, 36(4), 1333–1340.
<https://doi.org/10.1016/J.IJREFRIG.2013.02.017>
- Murshed, S. M. S., Leong, K. C., & Yang, C. (2008). Thermophysical and electrokinetic properties of nanofluids – A critical review. *Applied Thermal Engineering*, 28(17–18), 2109–2125.
<https://doi.org/10.1016/J.APPLTHERMALENG.2008.01.005>
- Nguyen, C. T., Desgranges, F., Roy, G., Galanis, N., Maré, T., Boucher, S., & Angue Mintsa, H. (2007). Temperature and particle-size dependent viscosity data for water-based nanofluids – Hysteresis phenomenon. *International Journal of Heat and Fluid Flow*, 28(6), 1492–1506.
<https://doi.org/10.1016/J.IJHEATFLUIDFLOW.2007.02.004>
- Poku. (2022). Pengolahan Cpo123. *Manajemen Agribisnis*, 06, 105–119.
- Prasetyo, A. B. (2015). Aplikasi Metode Taguchi Pada Optimasi Parameterpermesinan Terhadap Kekasaran Permukaan Dankeausan Pahat Hss Pada Proses Bubut Material St 37. *Mekanika*, 13(2), 86–97.

- Riedel, C., Alegria, A., Colmenero, J., & Tordjem, P. (2012). Polymer Rheology by Dielectric Spectroscopy. *Rheology*. <https://doi.org/10.5772/35145>
- Sangroniz, L., Fernández, M., & Santamaria, A. (2023). Polymers and rheology: A tale of give and take. *Polymer*, 271, 125811. <https://doi.org/10.1016/J.POLYMER.2023.125811>
- Setiyadi, Lourentius, S., Ariella W, E., & M.S. Prema, G. (2013). 1454-3343-1-Pb. *Teknik Kimia*.
- Utomo, D. R. (2022). Pemanfaatan Minyak Kelapa dan Minyak Canola Sebagai Cairan Pendingin Mesin Bubut Terhadap Kekasaran Permukaan. *Jurnal Teknosia*, 16(1), 31–38.
- Variasi, P., Cairan, C., Konsumsi, T., Dan, E., & Kasar, B. (2015). *Digital Repository Universitas Jember*.
- Vyavhare, K., Timmons, R. B., Erdemir, A., & Aswath, P. B. (2021). Tribological Interaction of Plasma-Functionalized CaCO₃ Nanoparticles with Zinc and AshlessDithiophosphate Additives. *Tribology Letters*, 69(2), 1–34. <https://doi.org/10.1007/s11249-021-01423-z>
- Wahab, H. A., Zahir Hussain Shah, S., Ayub, A., Sabir, Z., Sadat, R., & Ali, M. R. (2023). Heterogeneous/homogeneous and inclined magnetic aspect of infinite shear rate viscosity model of Carreau fluid with nanoscale heat transport. *Arabian Journal of Chemistry*, 16(5), 104682. <https://doi.org/https://doi.org/10.1016/j.arabjc.2023.104682>
- Widiyawati, S., Novareza, O., Sulistyarini, D. H., & Putro, W. W. (2020). Pengaruh Penggunaan Cairan Pendingin (Coolant) terhadap Keausan Pahat Bubut HSS. *Jurnal Rekayasa Mesin*, 11(3), 467–475. <https://doi.org/10.21776/ub.jrm.2020.011.03.19>

Wirawan sumbodo. (2008). *Teknik Produksi Mesin Industri*.

Zhao, J., Huang, Y., He, Y., & Shi, Y. (2021).
Nanolubricant additives: A review.
Friction, 9(5), 891–917.
<https://doi.org/10.1007/s40544-020-0450-8>